



## 1363 DIGI-MET® Depth gauges



1



### Model

- Stainless steel
- Protection class IP67
- LCD display 7.5 mm
- ISO 13385
- Locking screw
- L-shaped measuring rod

### Functions

- ON / OFF
- Set to zero at any point
- mm / inch switching
- **Quick-Start**
- **Quick-Lock** (key lock)
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

### Delivery


- 300 mm measuring range in plastic case
- 500 mm measuring range in wooden case
- Screw-on extended measuring bridges must be ordered separately (page 53)

▣	Measuring range		Length of beam mm	Reading		Error limit mm	Order no.	List price EUR
	mm	inch		mm	inch			
▪	0 - 300	0 - 12	150	0.01	.0005	0.03	1363 722	484.00
▪	0 - 500	0 - 20	150	0.01	.0005	0.04	1363 728	563.00



### Accessories

	Order no.	List price EUR
Data cable DATA VARIABLE to RS232	1997 501	57.00
Data cable DATA VARIABLE to digimatic	1998 501	73.00
Data cable DATA VARIABLE to USB	1998 720	82.00



Measuring range mm	a	e	d
300	11.6	10	28
500	11.6	10	28