

1998 / 0996 / 1997 Data cable





1997 501

Model

Length 2 m

0996 701

 For use with MarCom Professional software to transfer the measured results to PC, laptop or workstation

M	Description	Order no.	List price EUR
	Cable Opto for RS232	0996 701	77.00
	Cable Opto for USB	0996 705	147.00
	Cable DataVariable for RS232	1997 501	50.00
	Cable DataVariable for Digimatic	1998 501	64.00
	Cable DataVariable for USB	1998 720	72.00

1998 720

0145 Measuring tool set >>Extensions<<

0996 705





Model

 Pairs of measuring inserts, disc dia. 6 / 10 / 12.5 mm

1998 501

- Pair of measuring inserts with 60° cone, dia. 9 / 12.5 mm
- Pair of measuring inserts with cylindrical surfaces 1.5 mm
- Insert holder, right / left with thread M 2.5
- Allen wrench SW 1.2 mm
- For digital pocket calipers with max. jaw thickness of 3.5 mm

Delivery

Wooden box

M	1	Description	Order no.	List price
				EUR
		Measuring tool set, 14 pieces	0145 110	171.00








1326 Universal pocket caliper "Pocket Talent"





Model

- Stainless steel
- Protection class IP67
- Factory standard
- LCD display 7.5 mm
- Locking screw
- For internal and external measurements
- Individually adaptable on problematic tasks through measuring inserts with thread M 2.5

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232
 - + Digimatic + USB

Delivery

- Wooden box
- Measuring inserts No. 0710161* and 0710177* Planar surface Ø 4.8 mm / Ball inserts Ø 5.0 mm
- Setting standard

Models with measuring range 300 and 500 mm on page 56

M	Measuring range		Jaw length	Reading		Order no.	List price
	mm	inch	mm	mm	inch		EUR
	0 - 150	0 - 6	40	0.01	.0005	1326 932	359.00


Our all-round talent can be combined with all common types of measuring inserts for indicators with a standard M 2.5 thread. This way, the Pocket Talent offers you various solutions for numerous measurement applications.



0710161*



0710177*



0710166



0710167



0710163





Product video

Accessories	Order no.	List price
		EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Measuring inserts M 2.5	0710 161	3.60
Measuring inserts M 2.5	0710 163	5.40
Measuring inserts M 2.5	0710 166	4.90
Measuring inserts M 2.5	0710 167	3.40
Measuring inserts M 2.5	0710 177	6.80
Setting standard for Pocket Talent	1326 990	39.00
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00

















Model

M M

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust

mm

0 - 150

10 - 200

With long cross jaws for inner measurements

Wall thickness caliper

- Inside cross points

60

Locking screw

Functions

ON / OFF

0.01

- Quick-Start Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232

Delivery

Wooden case


653.00

1326 930

+ Digimatic + USB

housing and operating keys
nave an excellent chemical
1 1

2.4



variable	uala	output
1 Digim	otic I	LIĆD

Jaw length		Rea	ding	Order no.	List price	
mm	inch	mm	inch		EUR	
40	1.6	0.01	.0005	1326 918	503.00	



Measuring range

inch

0 - 6

0.4 - 8

Accessories	Order no.	List price
		EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00

.0005








Delivery

Wooden case



Model

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust
- Housing and operating keys have an excellent chemical resistance
- Inside cross points
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232
 - + Digimatic + USB

₩	Measuring range		Jaw I	Jaw length Reading Depth gau		Depth gauge	Order no.	List price	
	mm	inch	mm	inch	mm	inch			EUR
Scrib	Scribing caliper with carbide-tipped outer measuring surfaces								
	0 - 200	0 - 8	33	1.3	0.01	.0005	rectangular	1326 912	320.00
With	With flat measuring surfaces e.g. for outer recesses								
	0 - 150	0 - 6	40	1.6	0.01	.0005	round 1.5	1326 920	545.00



Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00




































Delivery

Wooden case

Model

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust
- Housing and operating keys have an excellent chemical resistance
- Inside cross points
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
 PRESET-Function
- (setting a numerical value)
- Variable data output RS 232
- + Digimatic + USB

M		Measuring range		Jaw I	Jaw length		Reading		List price
		mm	inch	mm	inch	mm	inch		EUR
Wit	With pointed jaws								
		0 - 150	0 - 6	40	1.6	0.01	.0005	1326 916	396.00
Wit	With fine measuring tips								
		0 - 150	0 - 6	40	1.6	0.01	.0005	1326 922	447.00



1998720 1998501



1997501

Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00

32










Delivery

Wooden case



Model

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust

Housing and operating keys have an excellent chemical resistance

- Inside cross points
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

М		Measuring range		Jaw length		Reading		Order no.	List price		
		mm	inch	mm	inch	mm	inch		EUR		
Mo	Moving jaws for measuring the distance between bores										
		10 - 210	0.4 - 8.3	75	3.0	0.01	.0005	1326 924	443.00		
Mo	Moving jaws + cross tips										
		N - 2NN	N - 8	65	25	N N1	0005	1326 928	476 NN		



Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00



























Model

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust
- Housing and operating keys have an excellent chemical resistance
- Inside cross points
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

ons Delivery

Wooden case

M	Measuring range		Jaw length		Reading		Order no.	List price		
	mm	inch	mm	inch	mm	inch		EUR		
Mea	Measuring tips angled inwards									
	0 - 150	0 - 6	40	1.6	0.01	.0005	1326 904	573.00		
Mea	Measuring jaws angled inwards									
	0 - 150	0 - 6	40	1.6	0.01	.0005	1326 908	489.00		



Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
data cable DATA VARIABLE to RS232	1997 501	50.00
data cable DATA VARIABLE to digimatic	1998 501	64.00
data cable DATA VARIABLE to USB	1998 720	72.00













Delivery

Wooden case









Model

- Protection class IP67
- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Measuring system is insensitive to cooling agents and dust
- Housing and operating keys have an excellent chemical resistance
- Inside cross points
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

M 🕌	Measuring range		Jaw I	Jaw length		Reading		List price		
	mm	inch	mm	inch	mm	inch		EUR		
Measuri	Measuring tips angled outwards									
	20.5 - 170	0.8 - 6.7	40	1.6	0.01	.0005	1326 906	568.00		
Measuri	Measuring jaws angled outwards									
	10.5 - 160	0.4 - 6.3	40	1.6	0.01	.0005	1326 910	562.00		



Accessories	Order no.	List price
		EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00













1351 DIGI-MET® Caliper with cross points













- Stainless steel
- LCD display 10 mm
- Protection class IP65
- Factory standard
- Locking screw
- Inside cross points 55 mm

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Deli	ivery
------	-------

Wooden case

М	7	Measuring range		Jaw length		Reading		Error limit	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
		0 - 250	0 - 10	80	3.2	0.01	.0005	0.03	1351 920	499.00

1354 DIGI-MET® Caliper with gripper points











Model

- Stainless steel
- LCD display 10 mm
- Protection class IP65
- Factory standard
- Locking screw Gripper points 55 mm

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- Hold
- PRESET-Function (setting a numerical value)

 Variable data output RS 232 + Digimatic + USB

Delivery

Wooden case

M	7	Measuring range		Jaw I	Jaw length		Reading		Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
		0 - 250	0 - 10	75	3.0	0.01	.0005	0.03	1354 520	590.00



1997501

1998720

Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00

1998501











1348 DIGI-MET® Universal calipers














Model

- Stainless steel
- Factory standard
- Protection class IP65
- LCD display 10 or 12.5 mm
- Locking screw
- For internal and external measurements
- Individually adaptable on problematic tasks through measuring inserts with thread M 2.5

Functions

- ON/OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Delivery

- Wooden box
- Without measuring inserts (correct measuring inserts with thread M 2.5 see pages 137 - 140)

Model "Pocket Talent" with measuring range 150 mm on page 29

M	7	Measuri	ng range	Jaw length		Reading		Error limit	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
		0 - 300	0 - 12	90	3.5	0.01	.0005	0.06	1348 722	607.00
		0 - 500	0 - 20	100	4.0	0.01	.0005	0.06	1348 728	778.00



Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00



1320 DIGI-MET® Pocket caliper with 40 mm inside cross points













Model

- Inductive measuring system, resistent to damp and sweat
- Stainless steel
- LCD display 7.5 mm
- DIN 862
- Locking screw
- Inside cross points
- Four way measurement

Functions

- ON/OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- Variable data output RS 232 + Digimatic + USB

Delivery

Plastic case

M		Measuring range		Measuring range Jaw length		Reading		Error limit	Depth gauge	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm	dia. mm		EUR
Wi	With DATA VARIABLE, with extra long cross points (40 mm)										
•		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	round 1.5	1320 518	395.00



Accessories	Order no.	List price
		EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to USB	1998 720	72.00











- Stainless steel
- Reading parts have a satin chrome finish
- Factory standard
- Locking screw
- Low-set master scale
- High-precision laser graduation on vernier and scale

Delivery	8,5	Ŋ
Cardboard		

M	7	Measuring range		Measuring range Jaw length		Reading		Error limit	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
		0 - 300	0 - 12	90	3.5	0.05	1/128	0.03	0262 503	271.00

1353 DIGI-MET® Caliper for external locking grooves













Model


- Stainless steel
- Protection class IP65
- Inductive measuring system
- LCD display 10 mm
- Locking screw
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232
 - + Digimatic + USB



Wooden case



М	7	Measuring range		Measuring range Jaw length		Reading		Error limit	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
		0 - 300	N - 12	90	3.5	N N1	0005	U U3	1353 522	4 91 NN



Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable DATA VARIABLE to RS232	1997 501	50.00
Data cable DATA VARIABLE to digimatic	1998 501	64.00
Data cable DATA VARIABLE to USB	1998 720	72.00











1352 DIGI-MET® Calipers for internal grooves













Model

- Stainless steel
- LCD display 7.5 mm
- Factory standard
- Locking screw
- Protection class IP65

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232
 - + Digimatic + USB

Delivery

Wooden case

M		Measuring range	Jaw length		Reading		Error limit	Order no.	List price
		mmm	mm	inch	mm	inch	mm		EUR
		10 - 160	25	1.0	0.01	.0005	0.06	1352 516	388.00
		20 - 160	40	1.5	0.01	.0005	0.06	1352 517	437.00
		26 - 200	60	2.3	0.01	.0005	0.06	1352 518	800.00
		30 - 250	80	3.1	0.01	.0005	0.06	1352 520	900.00
		35 - 300	100	3.0	0.01	0005	0.06	1352 522	030 NN

0258 Calipers for internal grooves



Model

- Stainless steel
- Reading parts have a satin chrome finish
- Factory standard

Locking screw


- Low-set master scale
- High-precision laser graduation on vernier and scale

Delivery

Cardboard box



M M	Measuring range	Jaw length		Reading	Error limit	Order no.	List price
	mm	mm	inch	mm	mm		EUR
	10 - 160	25	1.0	0.05	0.1	0258 501	144.00
	20 - 160	40	1.5	0.05	0.1	0258 502	192.00
	26 - 200	60	2.3	0.05	0.1	0258 503	295.00
	30 - 250	80	3.1	0.05	0.1	0258 504	333.00
	35 - 300	100	3.0	0.05	0.1	0250 505	272 በበ



•		. '	
Measuring range mm	a	b	C
10 - 160	0.9	3.0	25
20 - 160	2.0	5.0	40
26 - 200	3.0	7.0	60
30 - 250	4.0	8.5	80
35 - 300	5.0	10.0	100









